

PVC Coated Weld Mesh Cn-Gabion

低发浸塑电焊网



Wire Gauge	Aperture	Width	Length	Weight	ExW
g	cm	m	m	kg	\$
140	3	1	18	7	10.11
160	3	1	18	9	12.05
140	3	1.2	18	6	9.47
140	3	1.2	18	7	10.33
160	3	1.2	18	8	11.19
160	3	1.2	18	9	12.05
180	3	1.2	18	11	14.20
140	3	1.5	18	8	11.40
160	3	1.5	18	10	13.77
160	3	1.5	18	11	14.85
220	3	1.5	18	18	22.81
140	3	1.8	18	10	16.35
160	3	1.8	18	13	19.58
200	3	1.8	18	16	22.81
230	3	1.8	18	22	29.48
180	3	2	18	16	22.81
180	3	2	18	18	24.10
180	3	2	18	19	25.17
200	3	2	18	25	33.78
120	1in	1	18	7	10.33
140	1in	1	18	8	11.19
140	1in	1	18	9	12.91
160	1in	1	18	11	15.49
220	1in	1	18	15	21.30
120	1in	1.2	18	9	13.34
140	1in	1.2	18	11	15.49
160	1in	1.2	18	13	17.64
180	1in	1.2	18	14	18.50
200	1in	1.2	18	17	25.60
140	1in	1.5	18	13	19.15
180	1in	1.5	18	16	20.66
220	1in	1.5	18	23	32.06
140	1in	1.8	18	13	21.52
140	1in	1.8	18	15	23.88
160	1in	1.8	18	16	24.74
200	1in	1.8	18	22	30.12
140	1in	2	18	15	23.88
140	1in	2	18	17.5	26.03
160	1in	2	18	18	26.46
200	1in	2	18	23	30.12
220	1in	2	18	24	31.41
100	1/2in	1	18	6	9.68
120	1/2in	1	18	8	11.19
120	1/2in	1	18	9	12.69
130	1/2in	1	18	12	15.92

100	1/2in	1.2	18	7	11.40
120	1/2in	1.2	18	9	13.34
120	1/2in	1.2	18	10	14.42
120	1/2in	1.2	18	11	15.28
150	1/2in	1.2	18	14	18.50
90	1/2in	1.5	18	9	14.63
100	1/2in	1.5	18	11	16.78
100	1/2in	1.5	18	13	19.36
120	1/2in	1.5	18	15	21.52
100	1/2in	1.8	18	16	28.62
120	1/2in	2	18	18	33.13
120	1/2in	2	18	27	38.08